


10/2021

Mod: DCS9/6-AC

Production code: GH50TTSBECDD


MODEL: DCS9/6-AC

Overall Dimension (Width-Depth-Height) *open	mm	724x818x1529(2010*)
Packaging Dimension (WxDxH)	mm	760x840x1520
Gross weight	Kg	120
Net weight	Kg	110
Volume	mc	0,97



Interface



	Rack size	mm	500x500
	Max door /hood opening	mm	450
□	Max glasses/plate Height	mm	425/440
	General construction		double skin
	Door/hood Construction		double skin
	Tank construction		deep drawn
↘	Tank volume	liter	20
	Tank heating element	W	2.500
	Tank surface strainers		stainless steel
☑	Wash pump type		double flow
	Wash pump power	W	700
	Wash temperature	°C	55
↘	Boiler type		without pressure
	Boiler volume	liter	11
	Back-flow system		break tank
	Boiler heating element	W	8.000
⊕	Rinse booster pump		yes
	Rinse booster pump power	W	200
	Rinse temperature	°C	80
	Rinse water consumption	Liter /rack	2,6
	Optimal external water pressure	bar	1 - 4
🚰	Drain system		deep drain
	Drain pump		YES
▶	Rinse aid dispenser		YES
	Detergent dispenser		YES
👤/👤	Wash cycle	sec	110 - 150 - continuous
	Sanitation washing cycle 		YES
	Water softner	Continuous type	YES
⚡	Electric Power	W	8.700
	Electric Connection	V - ph - Hz	400V 3+N 50Hz
	Fuse	A	16
	Plates racks	n°1	YES
	Flat Rack	n°1	YES
▶	Cutterly Rack		YES
	Electric cable		YES
	Drain hose		YES
	Fill hose		YES

