

05/2018

# Mod: G7/M50I7

Production code: BBG50I77



**Diamond**  
catering equipment

DOMINA 700

# G50I77



## INDIRECT HEATING, GAS MONOBLOC

### SEE MORE TECHNICAL DATA:

External dimensions - WxDxH (cm)	70x73x85
Boiling pan capacity (lt)	50
Total power (kW)	12,5

### HIDE THE OTHER TECHNICAL DATA:

Boiling pan dimensions - ØxH (cm)	40x42
Weight (kg)	91
Volume (m3)	0,8

The 1.5 mm worktop is in AISI 304 with a moulded edges for collecting liquids. The pan is in AISI 304 with bottom AISI 316 for greater resistance to corrosion. The brass drain tap is equipped with a removable filter. The AISI 304 lid ensures minimal loss of steam and heat. Hot and cold water tap with swivel nozzle on worktop. Indirect gas versions (mod. I): AISI 304 interspace, stainless steel tubular burner with self-stabilizing flame. Pilot flame with thermocouple safety device. Piezo-electric ignition of the pilot. Safety valve with pressure gauge. Indirect electric versions (mod. I): AISI 304 interspace, power adjustment with 4-position switch, pressure gauge for the automatic control of the interspace steam, safety valve with gauge. The low pressure steam in the interspace heats evenly the surface of the pan (for both the indirect versions).

