

10/2021

Mod: TP2B/H-R2

Production code: TEMP2V2540-DM

| | | | |
|---|--|--|--|
| Modello - Model - Model - Gerätetyp | | TP2B/HG-R2 | |
| | | TP2B/HA-R2 | |
| | | TP2B/H-R2 | |
| | | | |
| | | | |
| Descrizione - Description - Description - Beschreibung | | 2 Doors | |
| Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes | | EN400x600 | |
| Range | | -20°C...-10°C | |
| Scheda Elettronica - Electronic card | | EVCO EVX214 | |
| Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus S = Statico-Static-Statique-Stille Kühlung V = Ventilato-Ventilated-Ventile-Umluftkühlung | | V | |
| Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen | l | 293 | |
| Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen | Lunghezza - Width -Largeur - Breite | mm | 1505 |
| | Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür | mm | 800/1250 |
| | Altezza - Height - Hauteur - Höhe | mm | 850 |
| | | | |
| Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen | Lunghezza - Width -Largeur - Breite | mm | 905 |
| | Profondità - Depth - Profondeur - Tiefe | mm | 600 |
| | Altezza - Height - Hauteur - Höhe | mm | 540 |
| | | | |
| Porte - Doors - Portes - Türen | | 2 | |
| Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung | | 4 coppie guide per porta - 4 pairs of slides per door 4 couples des glissières chaque porte 4 Paar Führungen pro Tür | |
| Serratura - Lock - Serrure - Schloss | | <input type="checkbox"/> | |
| Fondo inox - Stainless Steel bottom - Fond inox - Edelstahlgrundboden | | <input type="checkbox"/> | |
| Sbrinamento - Defrost - Dégivrages - Abtauen | Type | | Gas caldo - Hot gas - Gaz chaude - Heissem Gas |
| | N° Defrost in 24 hrs. | | 4 |
| | Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung | | |
| Compressor | | | |
| | Model | | NEU6217U |
| | Potenza - Power - Puissance - Leistung | Hp | 3/4 |
| Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung | watt | 520 | |
| Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp | GWP | | R290 / 3 |
| Quantità di refrigerante - Refrigerant quantity Quantité de réfrigérant - Kältemittelmenge | gr | | 120 |
| Potenza assorbita - Total Power - Puissance - Leistung | watt | | 500W -2,5A (700W - 3,5A) |
| | Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung | V | |
| Peso Netto - Net weight- Poids net - Netto Gewicht | kg | | 165 |
| | Volume - Volume - Volume - Volumen | mc | |
| Efficienza Energetica - Energy Efficiency Classe Énergie - Energieeffizienzklasse | | | D |
| Energia - Energy - Énergie - Energie | kWh / annum | | 2725 |
| Volume Netto - Net Volume - Volume Net - Nettoinhalt | l | | 275 |
| Classe Climatica - Climate Class - Classe Climatique - Klima Classe | | | 5 +40°C 40% |

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional



