

03/2021

# **Mod: WR-32X1-B**

**Production code: GBK 32**

# OEM ABW Bench Scales



## Built to withstand

the harshest working conditions, Aqua washdown scales are rated IP67 and feature a large removable stainless steel weighing pan. Ideal for food production, catering and industrial environments, precision load technology enables improved performance and greater efficiency during weighing and counting tasks. The dual 20mm-high digit front and rear displays enhance visibility and productivity for the user. Checkweighing is simple, with separate high, ok and low coloured LED indicators that change colour to alert the operator if a sample is under, over or within preset limits. Power is supplied by AC adapter or rechargeable battery, and auto power-off conserves battery life.

### Features

- IP67-rated for protection against water and dust
- External calibration allows for verification and adjustment with weights
- Sealed keypad protects against dirt and spills
- Overload protection helps prevent damage to internal components
- Solid ABS housing is durable for industrial use
- Heavy-duty rubber feet ensure stability of unit
- Bright LED display for easy viewing in most environments
- Checkweighing LEDs clearly show under, over and within acceptable limits
- Front and rear 20mm LED displays allow for dual use
- Zero-tracking feature ensures display returns to zero reading
- The auto power-off feature conserves battery life
- Rechargeable battery included for operation almost anywhere
- Stabilization time of within 1 second
- AC adapter included

### Accessories

Item number	Description
3022014061	In-use cover
2020014062	In-use cover (pack of 5)
2020014063	In-use cover (pack of 10)
3002014371	Hard carrying case
303149759	Vegetable Scoop (complete with fitting to scales)
303149760	Confectionery Scoop (complete with fitting to scales)
700660290	Calibration certificate

### Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing

Model	OEM ABW 3	OEM ABW 6	OEM ABW 15	OEM ABW 30
<b>Maximum Capacity</b>	3kg	6kg	15kg	30kg
<b>Readability</b>	0.5g	1g	2g	5g
<b>Repeatability (sd)</b>	1g	2g	5g	10g
<b>Linearity</b>	1g	2g	5g	10g
<b>Pan size</b>	300x210mm			
<b>Weighing units</b>	g, kg, lb, lb:oz, oz			
<b>Stabilisation time (sec)</b>	1			
<b>Calibration</b>	External calibration			
<b>Display</b>	Dual-display LED with 20mm-high digits			
<b>Power supply</b>	12VDC 800mA adaptor / Internal rechargeable battery			
<b>Operating temperature</b>	0° to 40°C			
<b>Housing</b>	ABS plastic			
<b>Overall Dimensions</b>	300x310x105mm			
<b>Net weight</b>	2.5kg			

We follow a policy of continuous improvement and reserve the right to change specification and pricing without notice. Standard terms and conditions of sale apply. Errors and omissions excepted.