







08/2012

# Mod: RBB/2

Production code: 10401201-0-0-G (V1 2X1)



**Diamond**  
catering equipment

Model	RBB/2	URA/P1	RBB/2+2	RBB/3+3	URB/P2	RBB/4+4
						
Production code	10401201-0-0-G	10402701-0-0-0	10401202-0-0-G	10401204-0-0-G	10402702-0-0-0	10401206-0-0-G
Description	Storage cabin 600L	Cooling unit for Storage cabin 600/850 L	Storage cabin 850L	Storage cabin 1200L	Cooling unit for Storage cabin 1200/1550 L	Storage cabin 1550L
No. and type of doors	2 Full	–	2 Full	2 Full	–	2 Full
No. and type of grid shelves	–	–	–	–	–	–
Light	no	–	no	no	–	no
Key lock	no	–	no	no	–	no
Range (°C)	–	+2° +8°	–	–	+2° +8°	–
Operating Mode	–	Ventilated	–	–	Ventilated	–
<b>External Dimensions</b>						
Width (mm)	1060	675	1060	1465	675	1870
Depth/with open doors (mm)	730 / 1205	495	995 / 1470	995 / 1670	495	995 / 1872
Height (mm)	1060	305	1060	1060	305	1060
<b>Internal Dimensions</b>						
Width (mm)	980	–	980	1385	–	1790
Depth (mm)	620	–	885	885	–	885
Height (mm)	980	–	980	980	–	980
Gross capacity (L)	720	–	1000	1400	–	1800
<b>Defrost</b>						
Type of defrost	–	By time	–	–	By time	–
No. of defrost in 24h	–	6	–	–	6	–
Evaporation of defrost water	–	Hot gas	–	–	Hot gas	–
<b>Compressor</b>						
Brand	–	Tecumseh	–	–	Tecumseh	–
Model	–	AE 4425 Y	–	–	AE 4430 Y	–
Power (hp)	–	–	–	–	–	–
Cooling power (W)	–	352	–	–	445	–
Evaporation temp. (°C)	–	-15	–	–	-15	–
Climate class (°C)	–	+32	–	–	+43	–
<b>Refrigerant</b>						
Type	–	R134a	–	–	R134a	–
Refrigerant quantity (g)	–	210	–	–	250	–
<b>Electronic Controller</b>						
Brand	–	Carel	–	–	Carel	–
Model	–	Easy	–	–	Easy	–
<b>Electrical</b>						
Power input (W/A)	–	260 / 2,05	–	–	360 / 2,80	–
Power supply (V/Hz)	–	230/50	–	–	230/50	–
220V/60Hz	–	no	–	–	no	–
<b>Packaging Details</b>						
Packed volume (m <sup>3</sup> )	0,60	0,17	0,60	0,81	0,17	1,02
Gross weight (kg)	92	29	105	126	30	156
Net weight (kg)	62	25	75	96	26	123