





08/2015

Mod: RDY-1C

Production code: 10405001-0-0-0 (V5-1)



Diamond
catering equipment

Model	RDY-1C	GF-1C	RDY-2C	GF-2C
				
Production code	10405001-0-0-0	10406701-0-0-0	10405002-0-0-0	10406702-0-0-0
Description	Waste Disposal Cooler 240 Lt.	Monoblock Cooling Unit	Waste Disposal Cooler 2x240 LT.	Monoblock Cooling Unit
No. and type of doors	1 Full	–	2 Full	–
No. and type of grid shelves	–	–	–	–
Light	no	–	no	–
Key lock	no	–	no	–
Range (°C)	–	+2° +8°	–	+2° +8°
Operating Mode	–	Ventilated	–	Ventilated
External Dimensions				
Width/ with cooling unit (mm)	735/1020	285	1465/1750	285
Depth/with open doors (mm)	870 / 1545	545	870 / 1545	545
Height (mm)	1290	745	1290	745
Internal Dimensions				
Width (mm)	655	–	1385	–
Depth (mm)	760	–	760	–
Height (mm)	1135	–	1135	–
Gross capacity (L)	565	–	1195	–
Defrost				
Type of defrost	–	By time	–	By time
No. of defrost in 24h	–	6	–	6
Evaporation of defrost water	–	Hot gas	–	Hot gas
Compressor				
Brand	–	Tecumseh	–	Tecumseh
Model	–	AE 4425 Y	–	AE 4430 Y
Power (hp)	–	–	–	–
Cooling power (W)	–	352	–	445
Evaporation temp. (°C)	–	-15	–	-15
Climate class (°C)	–	+32	–	+32
Refrigerant				
Type	–	R134a	–	R134a
Refrigerant quantity (g)	–	210	–	250
Electronic Controller				
Brand	–	Dixell	–	Dixell
Model	–	XR30CH	–	XR30CH
Electrical				
Power input (W/A)	–	260 / 2,05	–	360 / 2,80
Power supply (V/Hz)	–	220-230/50	–	220-230/50
220V/60Hz	–	no	–	no
Packaging Details				
Packed volume (m ³)	0,65	0,17	1,06	0,17
Gross weight (kg)	84	32	134	36
Net weight (kg)	76	29	121	30